

FEATURES:

- UTILIZES STANDARD CAT 3, 5, OR 6 CABLE
- USED WITH TALKBACK PAGE CONTROLS
- AESTHETICALLY PLEASING WHITE GRILLE
- BAKED ENAMEL FINISH
- INTEGRAL PLENUM RATED BACKBOX MEETS OR EXCEEDS A.S.T.M. E84 FLAME & SMOKE TEST
- FOUR SEISMIC TABS PROVIDED FOR ADDITIONAL MOUNTING INTEGRITY
- REPLACES A 2' X 2' OR 1/2 OF A 2' X 4' CEILING TILE

**DESCRIPTION:**

8" speaker assembly mounted in 2' x 2' grille with integral backbox.

Specifications:**SPEAKER ELEMENT**

Cone Diameter: 8" (20.32 cm)
Voice Coil Impedance: 45 Ohms

INPUT

Impedance: 45 Ohms nominal
Rated Power: 12 Watts

SPEAKER FREQUENCY RESPONSE

80 Hz to 15 kHz

ENVIRONMENT

Temperature: -4 ° to +131 °F (-20 to +55 °C)
Humidity: 0-95% Non-Condensing

HOUSING AND FINISH

Steel housing with a white baked on acrylic enamel finish

DIMENSIONS AND WEIGHT

23.75 "H x 23.75 "W x 3.75 "D (60.325 cm x 60.325 cm x 9.525 cm)
Weight: 5.5 lbs (2.49 kg)
Shipping Weight: 8.3 (3.83 kg)

ARCHITECTS' AND ENGINEERS

The V-9062 Lay-in Talkback Ceiling Speaker shall consist of a white two foot by two foot perforated grille, a speaker and integral backbox. The speaker assembly, housing and hardware shall be electrically and acoustically matched for a frequency response of 80 Hz to 15 kHz.

The speaker element shall be cone type with 5 oz (141.75 g) ceramic magnet. Diameter of speaker cone shall be 8.0" (20.32 cm). Voice coil diameter shall be .75" (1.91 cm). Voice coil impedance shall be 45 ohms. Speakers utilizing an 8-ohm impedance voice coil will not be acceptable.

The baffle shall be constructed with a single piece of perforated steel with a white baked on acrylic enamel finish. The backbox meets or exceeds A.S.T.M. E84 flame and smoke test and has a three hour burn rating (UL181).

Four seismic tabs provided for additional mounting integrity.

The maximum dimensions shall be 23.75 "H x 23.75 "W x 3.75 "D (60.325 cm x 60.325 cm x 9.525 cm). Weight shall be approximately 5.5 lbs (2.49 kg).

LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event, shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.