

FEATURES:

- BUILT-IN VOLUME CONTROL
- EXCELLENT FOR VOICE AND MUSIC REPRODUCTION
- WIDE SOUND DISPERSION
- ELECTRICALLY, ACOUSTICALLY MATCHED PARTS
- ATTRACTIVE SIMULATED WALNUT CABINET

**DESCRIPTION:**

Wall surface mounted speaker unit complete with 45 ohm speaker volume control and sloped baffle.

Specifications:**SPEAKER ELEMENT**

Cone Diameter: 8.0"

Voice Coil Impedance: 45 ohm

FREQUENCY RESPONSE

60 Hz to 12 kHz

POWER RATING

12 Watts

ENVIRONMENT

Temperature: -20 to +55°C (-4 to +131 °F)

Humidity: 0-95% Non-Condensing

HOUSING AND FINISH

The baffle is constructed of .5" (1.27 cm) particle board covered with a simulated walnut vinyl with light brown open-weave grille cloth

DIMENSIONS AND WEIGHT

10.6 "H x 9.7 "W x 5.2 "D (26.924 cm x 24.638 cm x 13.208 cm)

Weight: 4.4 lbs (1.98 kg)

Shipping Weight: 5.3 lbs (2.385 kg)

ARCHITECTS' AND ENGINEERS

The Wall Speaker, Model VC-1062A shall consist of a speaker, volume control and sloped baffle. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 60 Hz to 12 kHz.

The speaker shall be 8" (20.32 cm) in diameter and have a ceramic magnet weighing 5 ounces. The impedance of the speaker shall be 45 Ohm. The voice coil shall be .75" (1.91 cm) in diameter. Voice coil impedance shall be 45 ohm. Operating temperature shall be -20 to + 55 °C (-40 to + 131 °F).

The baffle shall be constructed of .5" (1.27 cm) particle board covered with simulated walnut vinyl and have a light brown open-weave grille cloth.

Maximum dimensions of the housing shall be 10.6 "H x 9.7 "W x 5.2 "D (26.924 cm x 24.638 cm x 13.208 cm). Approximate weight is 4.4 lbs (1.98 kg).

LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the re-placement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.