

## FEATURES:

- Wall Mountable
- Small Footprint
- Convenient Screw Terminal Connectors

## DESCRIPTION:

The VMT-2 is an audio isolation transformer. It may be used for magnetically coupling line level audio. Common uses include isolating ground references from one audio circuit to another.

## Specifications:

<b>INPUT</b> Impedance 600 Ohms nominal	<b>ENVIRONMENT</b> Temperature: Temperature -4° to +131° F (-20° to +55° C)
<b>OUTPUT</b> Impedance 600 Ohms nominal	<b>DIMENSIONS AND WEIGHT</b> 1.75 "Hx 3.75 "W x 1.25 "D (4.445 cm x 9.525 cm x 3.175 cm) Weight: 0.5 lbs. (.23 kg) Shipping Weight: 0.7 lbs ( 0.315 kg)

## ARCHITECTS' AND ENGINEERS

The audio isolation transformer, model number VMT-2 shall be used for magnetically coupling line level audio and isolating ground references from one audio circuit to another.

## LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the re-placement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

**This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.**

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.